

PDU SPECIFICATION SHEET FOR: UK, IEC, 19" HORIZONTAL & VERTICAL

This range of horizontal and vertical mounting PDUs are constructed using modular sockets and a black 1u aluminium shell. The majority are switched (unless specification requires otherwise) with a raised collar and cover, to protect from accidental switch off. Fitted power leads are 3m (approx) as standard, terminated with 13A UK plug. Some models have a 5m (approx) lead option, while other models have interchangeable power lead options. All PDUs fitted with the 13A UK lead are also available with IEC C14, IEC C20 and 16 amp industrial (aka Commando) plug options. A smaller selection of PDUs are available as 32 amp versions.

Socket Type - Plug	No of Sockets	Mounting Style	Switched
UK - UK	4, 6, or 8	19" Horizontal	Yes, except 8 way
IEC C13 - UK	6, 8, 10, 12 or 16	19" Horizontal	Yes, except 16 way
UK - UK	8, 10, 12 or 15	Vertical	Yes
IEC C13 & C19 Mixed – 16A Comm	20x C13 + 4x C19	Vertical	Yes
UK/IEC Mixed – UK Plug	5x UK, 5x C13	19" Horizontal	No
UK – 32A Comm	6, 12	Horizontal (6) Vertical (12)	No

