Excel Category 5E Cable U/UTP B2ca LS0H 305m Box - Violet

Item Code: 190-066





Product Overview

Excel Category 5e Unscreened Cables are manufactured and tested to the ISO 11801, EN 50173 and ANSI/TIA-568-C standards for enhanced performance Category 5 cables. Each cable consists of 8 colour coded polyethylene insulated conductors. These are twisted together to form 4 pairs with varying lay lengths.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

Product Specifications


Feature	Values
Category	5E
Overall screening	None
Conductor screening	None
Outer sheath colour	Violet
Reaction-to-fire class according to EN 13501-6	B2ca
Smoke development class according to EN 13501-6	sla
Euro class flaming droplets/particles according to EN 13501-6	dl
Euro class acidity according to EN 13501-6	al
AWG-size	24
Specification core insulation	PE
Core identification	Colour



Item Code: 190-066

Outer sheath material	Copolymer
Flame retardant	In accordance with EN 60332-1-2 and EN 50399
Outer diameter approx.	5 mm
Operating Temperature Range	-2060 °C
NVP value	65 %
Conductor category	Class $1 = $ solid
Total number of cores	8
Stranding element	Pairs
Conductor surface	Bare

Cross-section diagram



Cable specifications

Features	Values
MBR during installation	8x cable OD
MBR installed	4x cable OD
Pair-to-Ground Capacitance Unbalance	≤330pF/100m
Resistance Unbalance	0.02
Mutual Capacitance	≤5.6nF/100m
Coupling Attenuation	\geq 40 dB (Type III)

Item Code: 190-066



Max.Conductor DC Resistance @ 20 Deg.C	93.8 (Ohm/km)
Min.Insulation Resistance(Mohm.km)	5000
Dielectric strength	DC ,1KV/min

Standards

Applicable standard	Subject
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
EN 50173-1:2011	Information technology. Generic cabling systems - General requirements
EN 50173-2:2007 + A1:2010	Information technology. Generic cabling systems - Office premises
BS EN 50288-6-1:2013	Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2011	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A1:2013	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
RoHS	Restriction of Hazardous Substances - Compliant



Part Number Table

Part Number

190-066

Description

Excel Category 5E Cable U/UTP B2ca LS0H 305m Box - Violet

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.